

## 4 Wheel Electric Forklift Truck

Model	Unit	FE16SF	FE18SF	FE20SF
Power Type	-	Battery	Battery	Battery
Load Capacity	kg/lb.	1600/3520	1800/3960	2000/4400
Load Center	mm/in.	500/19.7	500/19.7	500/19.7
Max.Lift Height	mm/in.	3300/130.02	3300/130.02	3300/130.02
Fork Size(L*W*T)	mm/in.	920x100x35/ 36.25x3.94x1.38	920x100x38/ 36.25x3.94x1.50	1070x122x40/ 42.16x4.81x1.58
Tilt Angle (Fwd/Bwd)	deg	6 / 12	6 / 12	6 / 12
Length to Fork Face	mm/in.	2043/80.49	2050/80.77	2055/80.97
Overall Width	mm/in.	1070/42.16	1070/42.16	1120/44.13
Mast Lowered Height	mm/in.	2135	2135	2135
Overhead Guard Height	mm/in.	2000/78.80	2000/78.80	2000/78.80
Min.Right Angle Aisle Width	mm/in.	3634/143.18	3639/143.38	3644/143.57
Turning Radius (outside)	mm/in.	1940/76.44	1945/76.63	1950/76.83
Wheelbase	mm/in.	1360/53.58	1360/53.58	1360/53.58
Ground Clearance: Mast	mm/in.	100/3.94	100/3.94	100/3.94
Travel Speed	km/h	13.5/14.5	13.5/14.5	13.5/14.5
Weight (with battery)	kg/lb.	3230	3320	3476
Driving Motor	kw	6.5x2	6.5x2	6.5x2
Lifting Motor	kw	12	12	12
Battery: voltage/ capacity	V/Ah	48/460	48/460	48/460
Battery Weight	kg/lb.	800/1760	800/1760	800/1760
Type of Drive Control	-	SME	SME	SME
Transmission Case	-	PMP	PMP	PMP

## FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address: