

## Container Forklift

Model	Unit	CPCD50C	CPCD60C	CPCD70C
Power Type	-	Diesel	Diesel	Diesel
Load Capacity	kg/lb.	5000/11000	6000/13200	7000/15400
Load Center	mm/in.	600/23.64	600/23.64	600/23.64
Max.Lift Height	mm/in.	2500/98.5	2500/98.5	2600/102.44
Free Lift Height	mm/in.	1250/49.25	1250/49.25	1250/49.25
Fork Size(L*W*T)	mm/in.	1220x150x60/48.07x5.91x2.36		1220x150x65/48.07x5.91x2.56
Tilt Angle(Fwd/Bwd)	deg	6/12	6/12	6/12
Length to Fork Face	mm/in.	3440/135.54	3585/141.25	3585/141.25
Overall Width	mm/in.	1995/78.60	1995/78.60	1995/78.60
Overall Height Fork Raised	mm/in.	3400/133.96	3400/133.96	3400/133.96
Overhead Guard Height	mm/in.	2150/84.71	2150/84.71	2150/84.71
Min.Right Angle Aisle Width	mm/in.	2960/116.62	3000/118.2	3040/119.78
Turning Radius (outside)	mm/in.	3250/128.05	3300/130.02	3360/132.38
Travel Speed(with/without)	km/h	10/28	10/28	10/28
Lifting Speed(with/without)	mm/h	430	430	350
Max.Grade Ability	%	20	20	20
Ground Clearance:Mast	mm/in.	195/7.68		
Ground Clearance:Frame	mm/in.	195/7.68		
Wheelbase	mm/in.	2250/88.65		
Tread (Front/Rear)	mm/in.	1470(57.92)/1700(66.98)		
Self Weight	kg/lb.	8000/17600	8500/18700	9350/20570
Engine Model	-	ISUZU 6BG1		
Rated Output	kw/r.p.m	80.9 / 2500		
Rated Torque	NM/r.p.m	353 / 1600		
Displacement	cc	5785		

## FEED BACK FORM

E-mail:

Message:

Product Name:

Your Name:

Company:

FAX / TEL:

MSN/SKYPE

Address:

